



RODA GUIA COM RASPADOR (9 e 11 HASTES)

Optional guide wheel with scraper
Rueda guía con raspador opcional



SUPORTE PARA RODA GUIA OPCIONAL (9 E 11 HASTES)

Optional support for guide wheel.
Supuete rueda guía opcional



FIXAÇÃO COM PARAFUSOS E PINOS DE SÉRIE

Fixation with pin system of series
Sistema de fijacion con pin.



SUPORTE ADICIONAL OPCIONAL

Optional additional support
Apoyo adicional opcional



ASSISTA O VÍDEO



Ref. 00278 - AS 2500.9 P
com roda guia e raspador como acessório



Ref. 00271 - AS 1900.7 P



Ref. 00188 - AS 1400.5 JRP

Arados Subsoladores

Plow subsoiler / Arado subsolador

REF	MODELO	LARGURA	HASTES	SUPORTE PARA RODA GUIA	SUPORTE ADICIONAL	ESPESSURA HASTE	PROFUNDIDADE MÁXIMA	POTÊNCIA REQUERIDA	PESO
REFERENCE	MODEL	WIDTH	DRILL ROD	SUPPORT TO WHEEL GUIDE	SUPPORT ADDITIONAL	STEM THICKNESS	MAXIMUM DEPTH	REQUIRED POWER	WEIGH
REFERENCIA	MODELO	ANCHO	VARILLA	APOYO A LA RUEDA GUÍA	APOYO ADICIONALE	GRUESSA VARILLA	PROFUNDIDAD MÁXIMA	PROFUNDIDAD PRECISA	PESO
00188	AS 1400.5 JRP	1400 mm	5 Hastes Junior	ND	0	1.1/4"(31,75mm)	490mm	40 Cv	255 Kg
00183	AS 1600.5 JRP	1600 mm	5 Hastes Junior	ND	0	1.1/4"(31,75mm)	490mm	40 Cv	315 Kg
00270	AS 1600.5 P	1600 mm	5 Hastes Curvo	ND	0	1.1/4"(31,75mm)	550mm	60 Cv	320 Kg
00271	AS 1900.7 P	1900 mm	7 Hastes Curvo	ND	0	1.1/4"(31,75mm)	550mm	80 Cv	370 Kg
00155	AS 2350.7 P	2350 mm	7 Hastes Curvo	ND	0	1.1/4"(31,75mm)	550mm	80 Cv	460 kg
00278	AS 2500.9 P	2500 mm	9 Hastes Curvo	S	0	1.1/4"(31,75mm)	550mm	105 Cv	440 Kg
00316	AS 3100.11 P	3100 mm	11 Hastes Curvo	S	0	1.1/4"(31,75mm)	550mm	115 Cv	716 Kg